

eXF 9039 B

Gloss Chrome / Black

eMTB FULL SUSPENSION / eXF

Available from
April 2024



SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 750Wh
DISTANCE	200km
MAX. TORQUE	85Nm / 340%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17460 Condition 4 For rough Off-Road riding and jumps less than 120cm

E- BIKE PARTS

MOTOR	BOSCH Performance Line CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 750Wh
DISPLAY	BOSCH Mini Remote

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03.1, Advanced e-MTB Geometry, Travel 160/140 mm, BOSCH CX Performance 5G ready, Integrated 750Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	RockShox Lyrik Select RC, Tapered, DebonAir, 15x110mm axle, 160mm travel
REAR SHOCK	RockShox Super Deluxe Select R, size 230x65mm
HEADSET	ACROS AZX-1051S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO M6120, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

WHEELSET FRONT	DT Swiss H 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss H 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TYRE FRONT	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX SpeedGrip
TYRE REAR	Schwalbe Nobby Nic Evo, SuperTrail, TL-Easy, 29x2.60", ADDIX SpeedGrip

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 760mm, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizik Aidon X5, Alloy
SEAT POST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEAT POST CLAMP	ONE CC-904A, 34,9mm, Full CNC machined, Black

GEOMETRY

FRAME SIZE	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29
BB DROP (MM)	27	27	27
SEAT TUBE LENGTH (MM)	420	440	490
EFFECTIVE TOP TUBE LENGTH (MM)	610	630	650
STACK HEIGHT (MM)	625	625	625
REACH (MM)	465	485	505
SEAT TUBE ANGLE	77°	77°	77°
HEAD TUBE ANGLE	64°	64°	64°
REAR CENTER (MM)	446	446	446
HEAD TUBE LENGTH (MM)	120	120	120
WHEELBASE (MM)	1251	1271	1291
STEM (MM)	50	50	50
HANDLEBAR (MM)	760	760	760
CRANKSET (MM)	165	165	170
SEATPOST (MM)	150		