

X-ROAD 6.5 GF

Matte Black Stealth

ROAD & GRAVEL / GRAN FONDO



SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready
FORK	X-ROAD Carbon Fork
BOTTOM BRACKET	SHIMANO BB-R60, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.5x14L, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7120, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7120, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7100, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7100, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7120, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 140mm
BRAKE REAR	SHIMANO 105 R7120, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRE FRONT	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TYRE REAR	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal Gravel
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31,8mm, Black

GEOMETRY

FRAME SIZE	500mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	523	530	540	570	590
STACK HEIGHT (MM)	549	558	569	606	616
REACH (MM)	368	367	371	384	401
SEAT TUBE ANGLE	74,3°	73,8°	73,5°	73°	73°
HEAD TUBE ANGLE	71,5°	71,5°	72°	73°	73°
REAR CENTER (MM)	414	414	414	414	414
HEAD TUBE LENGTH (MM)	125	135	145	180	190
WHEELBASE (MM)	990	992	995	1010	1030
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	410	430
CRANKSET (MM)	170	170	172.5	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

superior.